


AD 220

Doosan
Mecc Alte
D+ &



ISO8528	GC,) &
SZUTEST	GC - \$\$\$
CE	

2000/14/EC	&\$\$\$#(#
	z) \$ z' \$z 'D:

	"	"	"	"	Amp
400/230	220,00	176,00	20,00	160,00	288,00

fPQDE	GC,)	
fDFDE	GC" \$(*	z&(

Standard Specifications

z

fl ! E

z

z

ALTERNATOR

D: A Z 5JF

fl

z

fPQ \$\$\$ \$\$\$

E

TRANSFER SWITCH

fl

z

z

z



AD 220

Doosan
Mecc Alte
D+' &'

Manufacturer		Doosan		
Model		P086TI		
		% \$\$\$' "# "		
		% - \$\$\$' "		
		Q* + \$\$\$ < DQ		
	L	8,070		
	"	111X139		
		16,4:1		
	fl # ı	"# "	1500	
	fl ı	L	15,50	
		L	48,50	
AbsorbedAirDischargeReSourceKey.Text	' # "	12,10		
	' # "	250,00		
fl ' # ı	' # "	34,00		
	° C	580,00		
		24 V d.c.		
	Load	% \$i	ııı) \$i
	# "			
		43,10	31,70	21,10

		Mecc Alte		
		ECO 38 2SN/4		
	Hz	50		
	"	200,00		
7cg'		0,80		
		3		
	fl ı	400/230		
	A	288,00		
Temperature		H		

		fl ı		fl ı	
	"	"	"	"	L
AD 220	1800,00	2688,00	1150,00	1624,00	380,00
		fl ı		fl ı	
	"	"	"	"	L
AK 50	2175	3400	1217	1938	380

AD 220

Doosan
Mecc Alte
D+ &

f@#@Bt
f@#@Bt

"z" "z"

f@#@Bt

971

f&%) +L

f&)(, t

f&% \$L

ž

"% !&*(

&(\$)

ž

ž

GA 8


!&+""

ž

"Новая энергия"

AD 220

Doosan
Mecc Alte
D+ &''



- 1 Steel structures
- 2 Emergency stop push button
- 3 Control panel is right side of the set.
- 4 Corrosion-resistant locks and hinges
- 5 Sump drains valves
- 6 Sound proof foam material
- 7 Lifting Points

"Новая энергия"

	"	1217
fl "L	"	3400
fl "L	"	1938
	L	380