

AD 330

Doosan
Mecc Alte
D+ &



ISO8528

GC ;) &

SZUTEST

GC - \$\$\$



2000/14/EC

&\$\$\$#(#

z) \$ z' z' D:

	"	kw	"	kw	Amp
400/230	330,00	264,00	300,00	240,00	433,00

fP GDE

GC ;) &

) & z

fDF DE

z & (

GC

Standard Specifications

z

fl

E

z

z

ALTERNATOR

D; A Z 5J F

TRANSFER SWITCH

AD 330

Doosan
Mecc Alte
D+' &'

Manufacturer		Doosan		
Model		P126TI-II		
		% \$ \$	"# "	
		294,00 kw [394,00HP]		
	L	11,050		
	"	123 x 155		
		17,0:1		
	fl # ı	"# "	1500	
	fl ı	L	23,00	
		L	65,00	
Absorbed Air Discharge ReSourceKey.Text	' # "	20,10		
	' # "	295,00		
fl ' # ı	' # "	47,40		
	° C	590,00		
		24 V d.c.		
	Load	% \$ \$ı	ı %)) \$ı
	# "			
		63,10	47,00	31,30


		Mecc Alte		
		ECO 38-2LN/4		
	Hz	50		
	"	300,00		
7 cg		0,80		
		3		
	fl ı	400/230		
	A	433,00		
Temperature		H		

		fl ı		fl ı	
	"	"	"	"	L
AD 330	2375,00	2950,00	1300,00	1588,00	450,00
		fl ı		fl ı	
	"	"	"	"	L
MS 60	3065	3960	1356	2097	470

AD 330

Doosan
Mecc Alte
D+' &'

1 D+' &'



2

8G9ž + ' &\$ž) 5ž&&\$#(\$

3

4

5

8G9+' &\$
&&\$' ž

8G9+' &\$

8G9+' &\$

% &1*(
žFG' &žFG(,) ž

"Новая энергия"

AD 330

Doosan
Mecc Alte
D+ &

f@#@Bt
f@#@Bt

"z" "z"

f@#@Bt

971

f&%) +L

f&)(, t

f&% \$L

z

% !&*(

&(\$)

z

z

GA 8

!&+""

z

6G'9B *\$-\$) \$


6G'9B *%\$\$\$!*!&

6G'9B *%\$\$\$!*!(

"Новая энергия"

AD 330

Doosan
Mecc Alte
D+ &



- 1 Steel structures.
- 2 Emergency stop push button.
- 3 Control panel is mounted on the baseframe . Located at the right side of the generator set.
- 4 Corrosion-resistant locks and hinges.
- 5 oil could be drained via valve and a hose
- 6 Exhaust system in the canopy.
- 7 special large access doors for easy maintenance
- 8 in front and back side special large access doors for easy maintenance
- 9 Base frame -fuel tank.
- 10 Lifting points similar to ISO container , located on each top corner of the canopy
- 11 the canopy provides easy access to radiator cap.
- 12 sound proofing materials
- 13 Plastic air intake pockets.

ООО "Новая энергия"

	"	1356
fl "L	"	3960
fl "L	"	2097
	L	470